

REA Guidance Project EZ Guide 250 Help Guide

QUICK START MENU

- On the WELCOME page hit OK
- Select English – press OK
- Select US units – press OK
- Use the up/down buttons to highlight 'Many Trees/Buildings' and press OK
- Display Quick Start Wizard – highlight 'Yes' and press OK

GUIDANCE SETUP

- Use the up/down arrows to highlight the wrench icon – Press OK
- Highlight 'User Mode' – Press OK
- Select Advanced – Press OK
- Use the up/down arrows to highlight the wrench icon – Press OK
- Highlight 'System' – Press OK
- Select Guidance – Press OK
 - Check to make sure Coverage Logging is set to Engaged
 - Check to make sure Look Ahead is set to 1 sec
 - If either of these settings is incorrect highlight and make change
 - Once settings are confirmed select the return button by pressing the I button on the left side of the display 3 times.
- Select the return button by pressing the I button on the left side of the display
- You are now back on the main guidance screen
- Highlight the reset button (top right side) and Press OK to start a new field

CREATING A NEW FIELD

- Highlight 'Create New Field' – Press OK
- Highlight 'Client' and press OK
- Highlight correct REA name and press OK
- Highlight 'Farm' and press OK
- Select the appropriate guidance tool (whether they are using EZ-Guide for guidance or different method) from the list, highlight it and press OK
- Leave 'Field' set to Default_field
- Highlight 'Event' and press OK
- Select the appropriate equipment setup from the list, highlight it and press OK
- Highlight 'Continue' at the top of the Confirm Configuration page and Press OK
 - Use up/down arrows to select your boom/implement width; when correct width is reached press OK
 - Use up/down arrows to set overlap to 12"; when correct width is reached press OK

- Use the up/down arrows to select the distance the implement is from the antenna (for example if your boom is 12' from where the antenna is placed on the cab of the tractor, enter 144") – when correct distance is reached Press OK
- Use up/down buttons to select 0" (only change this if your implement is offset to one side from the center of your tractor); Press OK
- Highlight the pattern type you wish to use (see manual or quick reference guide for explanation of pattern types) – Press OK
- You are now at the main guidance screen

COVERAGE LOGGING

- **Make sure the coverage logging feature is turned ON for the project regardless of whether the operator is using the system as their guidance tool or not**
- Turn coverage logging on by pressing the second button on the left side. When activated you will see the tractor icon on the left side change to look like it is applying a product.
- When you are finished with a field select the reset icon at the top right and press OK
- You will be asked if you are finished with the current field – select yes and press OK
- Press the back arrow on the left hand side to return to the home page
- Press the reset button to start a new field

DOWNLOADING FILES

- Place USB into slot in back of EZ Guide 250 when unit is powered OFF.
- Power on EZ Guide 250
- On the WELCOME page hit OK
- Select English – press OK
- Select US units – press OK
- Display Quick Start Wizard – highlight 'Yes' and press OK
- You will see a message at the bottom of the screen page that the USB is ready for use – wait until you see this message before continuing
- Highlight 'Data Management' – Press OK
- Highlight 'Manage Fields' – Press OK
- Select Send Summary Reports to USB and then press OK. The *Send Summary to USB* screen appears.
- Select All to send all summary reports to the USB drive.
- Select Send and then press OK